

Pocket Wagon

Pocket wagon
Wagon poche

Taschenwagen
Vagone tasca

Technical data

Length over buffers	20 500 mm
Loading length	12 200 mm
Loading width	2 438 mm
Loading platform above the rail	475 mm
Tare weight	23.5 t
Payload ca.	66.5 t
Minimum curve	35 m
Maximum speed	120 km/h

Technische Daten


Länge über Puffer	20 500 mm
Ladelänge	12 200 mm
Ladebreite	2 438 mm
Höhe der Ladeplattform über Schiene	475 mm
Eigengewicht	23.5 t
Lastgrenze	66.5 t
Min. befahrbarer Kurvenradius	35 m
Max. Geschwindigkeit	120 km/h

Données techniques

Longueur hors tout	20 500 mm
Longueur utile	12 200 mm
Largeur utile	2 438 mm
Hauteur du plancher utile	475 mm
Tare	23.5 t
Limite de charge	66.5 t
Rayon de courbure minimum	35 m
Vitesse maximum	120 km/h

Dati tecnici

Lunghezza sopra respingenti	20 500 mm
Lunghezza di carico	12 200 mm
Larghezza di carico	2 438 mm
Altezza della piattaforma	475 mm
Tara	23.5 t
Carico utile	66.5 t
Raggio min. di curvatura	35 m
Velocità massima	120 km/h



These wagons were built in 1998 in Finland and are approved for UK domestic traffic only. The pocket wagon feature of these wagons has been designed to accommodate either 2 x 20' or 1 x 40' containers up to 9'6" high within the UK domestic structure gauge.

Payload	A	B	C	D
S	40.5	48.5	58.5	66.5
SS	40.5	48.5	66.5	